

Flow Rate (lb/hr CO2)	MFI Model	Port (in)	Replacement Element P.N.	Effective Life Based on 0.1 ppm Contaminant Conc. (hrs)		
				Hydrogen Sulfide	Carbonyl Sulfide	Benzene
60 lb/hr	PAKSG05-025	1/4"	SG03-10-DU-1X	768	267	467
			SG03-10-DU-2X	1229	427	747
	PAKSG05-050	1/2"	SG03-10-DU-1X	767	267	467
			SG03-10-DU-2X	1229	427	747
60 lb/hr	PAKSG08-025	1/4"	SG05-10-DU-1X	1536	533	933
			SG05-10-DU-2X	2458	853	1494
	PAKSG08-050	1/2"	SG05-10-DU-1X	1536	533	933
			SG05-10-DU-2X	2458	853	1494
120 lb/hr	PAKSG08-025	1/4"	SG05-10-DU-1X	768	267	467
			SG05-10-DU-2X	1229	427	747
	PAKSG08-050	1/2"	SG05-10-DU-1X	768	267	467
			SG05-10-DU-2X	1229	427	747
120 lb/hr	PAKSG10-025	1/4"	SG07-10-DU-1X	1075	373	653
			SG07-10-DU-2X	1722	598	1046
	PAKSG10-050	1/2"	SG07-10-DU-1X	1075	373	653
			SG07-10-DU-2X	1722	598	1046
300 lb/hr	PAKSG13-075	3/4"	SG09-13-DU-1X	704	244	428
			SG09-13-DU-2X	1124	391	685
	PAKSG13-100	1"	SG09-13-DU-1X	704	244	428
			SG09-13-DU-2X	1124	391	685
1,000 lb/hr	CHCC4-FF3-300-F	3"	SG-38-51-DU-1X	4608	1600	2800
			SG-38-51-DU-2X	7373	2560	4480
2,000 lb/hr	CHCC4-FF3-300-F	3"	SG-38-51-DU-1X	2304	800	1400
			SG-38-51-DU-2X	3686	1280	2240
4,000 lb/hr	CHCC4-FF3-300-F	3"	SG-38-51-DU-1X	1152	400	700
			SG-38-51-DU-2X	1843	640	1120
6,000 lb/hr	CHCC4-FF3-300-F	3"	SG-38-51-DU-1X	768	267	467
			SG-38-51-DU-2X	1229	427	747
6,000 lb/hr	CHCC4-FF3-300-F	3"	SG-38-51-DU-1X	1536	533	933
			SG-38-51-DU-2X	2458	853	1493
6,000 lb/hr	CHCC4-FF61201-600-F	6"	SG-38-51-DU-1X	1536	533	933
			SG-38-51-DU-2X	2458	853	1493
8,000 lb/hr	CHCC4-FF61201-600-F	6"	SG-38-51-DU-1X	1152	400	700
			SG-38-51-DU-2X	1843	640	1120
8,000 lb/hr	CHCC4-FF61603-600-F	6"	SG-38-51-DU-1X	1728	600	1050
			SG-38-51-DU-2X	2765	960	1680
10,000 lb/hr	CHCC4-FF61201-600-F	6"	SG-38-51-DU-1X	922	320	560
			SG-38-51-DU-2X	1495	512	896
10,000 lb/hr	CHCC4-FF61603-600-F	6"	SG-38-51-DU-1X	1382	480	840
			SG-38-51-DU-2X	2212	768	1344
12,000 lb/hr	CHCC4-FF61201-600-F	6"	SG-38-51-DU-1X	1536	533	933
			SG-38-51-DU-2X	2458	853	1493
12,000 lb/hr	CHCC4-FF61603-600-F	6"	SG-38-51-DU-1X	1152	400	700
			SG-38-51-DU-2X	1843	640	1120
12,000 lb/hr	CHCC4-FF12-1200-F	12"	SG-38-51-DU-1X	4224	1467	2567
			SG-38-51-DU-2X	6758	2347	4107