

SYM	ECN	DATE	
Α	6371	7-28-03	
В	7065	1-20-05	

MATERIALS OF CONSTRUCTION

ELEMENT TYPE A ± .03 B REF C

CFCC-35-X01-DU

3.02 DIA

MEDIA: BOROSILICATE GLASS/EPOXY

RETAINER: PLATED CARBON STEEL

DRAIN LAYER: POLYESTER/RAYON (A)

HANDLING NET: POLYPROPYLENE

ENDSEALS: **POLYURETHANE RUBBER**

FLOW DIRECTION: IN TO OUT

MAXIMUM PEAK TEMPERATURE: 225°F

MAXIMUM OPERATING TEMPERATURE: 175°F

\ _	GRADE	COALESCING EFF. (%) RATING	OIL CARRYOVER (PPM _W) ⁽¹⁾	RATED FLOW SCFM AT 100 PSIG (SCFM/IN ²)	NOMINAL PRESSURE DROP AT RATED FLOW (PSID)	
					DRY	WET
	2	99.999+	.001	1.8	1.50	5-8
	4	99.995	.003	2.5	1.25	4-6
	6	99.97	.008	3.3	1.00	3-5
	8	98.5	.200	4.5	0.50	2-3
	10	95	.830	5.5	0.50	1-2

4.00 DIA

28-1/8 +- 1/8

(1) TESTED PER ANSI/CAGI ADF-400 AT 40 PPMW OIL INLET. DOES NOT INCLUDE VAPORS.

SPEC SHEET COMPLETED BY

DATE

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

DNH	1-21-94
CHK BY	scale NTS

DRAWING No.

CFCC-35-X01-DU

